

# THE THERMAL-LUBE

## BIODEGRADABLE GL-5 GEAR OIL

# XL9532

June 2024

**XL9532** is a Readily Biodegradable Synthetic Gear Oil specifically designed to meet the environmental requirements of mobile equipment operating in sensitive areas.

**XL9532** Bio 80W90 GL-5 is designed to meet/exceed the SAE J306 and SAE J2360 requirements for manual transmissions, differentials, and heavy equipment transfer cases.

**XL9532** bio-based formula combine a bio-synthetic base stocks with a new high performances additive package to provide a super high viscosity index (VI). The result is an inherently biodegradable product which has the long-life heat stability, but which additionally offers the protection advantages of increased gear life through extremely high film strength and excellent low temperature performance.

### APPLICATION:

**XL9532** is recommended for industrial gears, manual transmissions, differentials, and heavy equipment transfer cases.

Consult the manual of the manufacturer for the appropriate grade.

Using Thermal-Lube's **COAT® system analysis program**, Thermal-Lube can certify that your equipment uses a Readily Biodegradable fluid that meets the OECD 301B standard.

### BENEFITS:

- Readily Biodegradable (OECD 301B  $\geq$  60%)
- Low aquatic toxicity
- Composed from a minimum of 80% renewable material
- Efficient operation over a wide temperature range
- Excellent hydrolytic and thermal stability - keep the system clean longer
- Exceptional oxidation stability allows extension of the intervals between oil changes
- High viscosity index - effective lubrication at high operating temperatures and very good performance at low operating temperatures
- Compatible with hydrocarbon and synthetic PAO based gear oils
- Compatible with a large range of seals (NBR, HNBR, AU an FPM).

### AVAILABILITY:

20 liters, 60 liters, 205 liters and 1000L.



255 Ave Labrosse, Pointe-Claire, Québec, Canada H9R 1A3

T: +1.514.694.5823; [www.thermal-lube.com](http://www.thermal-lube.com)

The information presented in this bulletin is, to the best of our knowledge accurate. It is intended to be helpful, and not considered to be a guarantee. L'information donnée dans ce bulletin est, au meilleur de nos connaissances, exacte. L'intention de ce bulletin est pour votre aide et non une garantie.

# BIODEGRADABLE GL-5 GEAR OIL

# XL9532

## TYPICAL SPECIFICATIONS

Product code: XL9532	/759	/809
SAE Grade	75W90	80W90
Viscosity (cSt @ 40°C) (ASTM D445)	90	112
Viscosity (cSt @ 100°C) (ASTM D445)	15.5	17.9
API Classification	GL-5	
AGMA Grade	4EP	
Viscosity Index (ASTM D2270)	183	177
Flash Point (°C)	>210	>220
Pour Point (°C) (ASTM D97)	-43	-38
Density (g/ml)	0.92	0.93
Colour	Light Yellow	
OECD 301B 28 Days % Biodegradation	>60	



255 Ave Labrosse, Pointe-Claire, Québec, Canada H9R 1A3

T: +1.514.694.5823; [www.thermal-lube.com](http://www.thermal-lube.com)

The information presented in this bulletin is, to the best of our knowledge accurate. It is intended to be helpful, and not considered to be a guarantee. L'information donnée dans ce bulletin est, au meilleur de nos connaissances, exacte. L'intention de ce bulletin est pour votre aide et non une garantie.