

THE THERMAL-LUBE

SYNTHETIC PAO COMPRESSOR OIL

XL7330

July 2022

XL7330 series of synthetic polyalphaolefin compressor fluids are recommended for a wide range of service conditions ranging from intermittent light loads to continuous heavy duty applications.

XL7330 fluids exhibit superior anti-wear characteristics and water tolerance, while protecting against oxidation and corrosion.

XL7330 fluids are designed to prevent gumming, sludge, resin, and carbon formation in valves and other working parts of compressors with excellent filtration.

XL7330 meets the strictest criteria of compressor manufacturers.

Available in all ISO standard viscosity grades or custom-formulated to suit any need.

ADVANTAGES:

- Non Carbonizing
- Anti Wear, Anti Foam
- Highly Resistant to Chemical Breakdown
- High Temperature Stability

FOR USE IN:

- Rotary Vane compressors
- Screw compressors
- Piston compressors

TYPICAL SPECIFICATIONS								
Product Code: XL7330	/022	/032	/046	/068	/100	/150	/220	/922
ISO Grade	22	32	46	68	100	150	220	Multi
Viscosity (cSt @ 40°C) (ASTM D445)	21.5	29.3	41.5	63.5	97.2	148.3	225	25.7
(cSt @ 100°C) (ASTM D445)	4.8	5.8	7.3	9.9	13.5	18.7	25.9	6.9
Viscosity Index	151	145	141	140	139	142	147	253
Flash Point (°C)	202	210	214	222	225	225	235	208
Pour Point (°C) (ASTM D97)	-58	-47	-40	-40	-35	-30	-32	-55
Specific Gravity (g/ml)	0.85	0.85	0.86	0.87	0.87	0.88	0.88	0.87
Colour	Blue or Clear							



255 Ave Labrosse, Pointe-Claire, Québec, Canada H9R 1A3

T: +1.514.694.5823; www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge accurate. It is intended to be helpful, and not considered to be a guarantee. L'information donnée dans ce bulletin est, au meilleur de nos connaissances, exacte. L'intention de ce bulletin est pour votre aide et non une garantie.