

THE THERMAL-LUBE

REFRIGERATION COMPRESSOR OIL

XL7337

July 2022

XL7337 series are high performance lubricating fluids formulated for use as refrigeration compressor oils. **XL7337** is recommended for all working conditions, from light, intermittent loads to continuous heavy loads.

XL7337 compressor oils contain ashless dispersants to keep "sticky" compressor valves clean.

XL7337 offers exceptional thermal and chemical stability providing a longer life fluid with less frequent oil change-outs.

XL7337 has been formulated to be fully compatible with most of the common refrigeration gases.

XL7337 meets the strictest criteria of compressor manufacturers.

TYPICAL SPECIFICATIONS			
Product Code: XL7337	/032	/068	/100
ISO Grade	32	68	100
Viscosity (cst @ 40°C) (ASTM D445) (cst @ 100°C) (ASTM D445)	29.3 4.5	63.5 6.7	101.2 8.9
Flash Point (°C)	174	187	198
Pour Point (°C)	-45	-37	-21
Specific Gravity (g/ml @ 15°C) (ASTM D1298)	0.904	0.910	0.910
Floc Point (°C)	-54	-48	-37
Dielectric Strength (kV) (ASTM D877)	35+	35+	35+
Aniline Point (°C)	81	88	84
Sealed Tube % R-22, 14 days+	0.20	0.30	--
Colour (ASTM D-1500)	0.5	0.5	3.0



255 Ave Labrosse, Pointe-Claire, Québec, Canada H9R 1A3

T: +1.514.694.5823; www.thermal-lube.com

The information presented in this bulletin is, to the best of our knowledge accurate. It is intended to be helpful, and not considered to be a guarantee. L'information donnée dans ce bulletin est, au meilleur de nos connaissances, exacte. L'intention de ce bulletin est pour votre aide et non une garantie.