

# THE THERMAL-LUBE

## SYNTHETIC AUTOMATIC TRANSMISSION FLUID

# XL7390

July 2022

**XL7390** is formulated from synthetic base stocks to provide longer parts life and smooth, positive gear shifting.

**XL7390** exhibits excellent high and low temperature stability and maintains a high degree of shear stability under severe operating conditions.

**XL7390** meets or exceeds the following specifications:

- Dextron III<sup>®</sup>, Dextron II<sup>®</sup>, Dextron<sup>®</sup>
- Mercon II<sup>®</sup>, Mercon<sup>®</sup>
- Type A Suffix A, Type A
- Ford M2C-138C, M2C-166H,
- Allison C-4
- Caterpillar TO-2, TO-4

Also: Sperry-Vickers, Denison, & Sundstrand pump systems

TYPICAL SPECIFICATIONS	
Product Code: XL7390	/030
Viscosity (cSt @ 40°C) (ASTM D445) (cSt @ 100°C) (ASTM D445)	35.5 7.5
Viscosity (cP @ -40°C) (ASTM D2983) (cP @ -35°C) (ASTM D2983) (cP @ -30°C) (ASTM D2983) (cP @ -20°C) (ASTM D2983)	16,000 7,600 3,200 950
Viscosity Index	186
Flash Point (°C)	225
Pour Point (°C) (ASTM D-97)	-55
Copper Strip Test (163°C for 3 hours)	Pass
Specific Gravity (g/ml)	0.86
Seal Swell	Pass
Foam Test	Pass*

DEXTRON<sup>®</sup> is a Registered Trademark of General Motors  
MERCON<sup>®</sup> is a Registered Trademark of Ford



255 Ave Labrosse, Pointe-Claire, Québec, Canada H9R 1A3

T: +1.514.694.5823; [www.thermal-lube.com](http://www.thermal-lube.com)

The information presented in this bulletin is, to the best of our knowledge accurate. It is intended to be helpful, and not considered to be a guarantee. L'information donnée dans ce bulletin est, au meilleur de nos connaissances, exacte. L'intention de ce bulletin est pour votre aide et non une garantie.